



TURBO 15W-40 MOTOR OIL

PRODUCT DESCRIPTION:

TURBO SAE 15W-40 Motor Oil is a multi-functional, mineral oil based product. It is formulated to provide optimum lubrication to a wide range of passenger cars and light commercial vehicles. TURBO SAE 15W-40 Motor Oil exceeds ACEA A3 and API SJ for modern gasoline engines, ACEA B3 and API CF for diesel engines, and is approved by Mercedes-Benz and Volkswagen. TURBO SAE 15W-40 Motor Oil has been proven in turbocharged engines and is compatible with catalytic converters.

CHARACTERISTICS:

- excellent wear protection
- prevents the formation of sludge and varnish
- high level of oxidation resistance
- protects against corrosion

SPECIFICATIONS AND APPROVAL

API SJ/CF	VW 501.01 (1/97)
ACEA A3, B3 (98)	VW 505.00 (1/97)
MB 229.1	
Peugeot-Citroen Meets PSA A & D requirements	

TYPICAL PROPERTIES:

SAE		15W-40
Density (15.6 °C)	kg/l	0.8837
Viscosity 100 °C	cSt	14.0
Viscosity 40 °C	cSt	102.0
Viscosity Index		139
Flash point (ASTM D-92)	°C	209
Sulphated ash	% Weight	1.32
T.B.N. (ASTM D-2896)	mg KOH/g	9.8
Pour point	°C	-27

Pennzoil Products Company

Note that the data quoted in this document are typical values and for indicative purposes only. The values do not constitute a commercial offer. Pennzoil Products Company reserves the right to amend product specifications without prior notice.