



### PRODUCT DESCRIPTION:

ULTRA TURBO is a semi-synthetic engine oil for optimum lubrication of modern gasoline, LPG and diesel engines in passenger cars and light commercial vehicles. Ultra Turbo Motor Oil has been proven in turbocharged engines and is compatible with catalytic converters. It exceeds the highest performance standards defined for gasoline engine oils.

### CHARACTERISTICS:

- protects the engine during cold starts
- excellent protection against wear and corrosion
- demonstrated fuel economy
- approved by Volkswagen
- for all Mercedes-Benz passenger cars

### SPECIFICATIONS AND APPROVAL

ULTRA TURBO exceeds the requirement off all major car manufacturers and the following Industry standards:

API: SL/SJ/CF	VW 500.00 (1/97)
ACEA: A3, B3(98)	VW 505.00 (1/97)
Mercedes-Benz 229.1	

### TYPICAL PROPERTIES:

SAE			<b>10W-40</b>
Density (15.6 °C)	kg/l	0.	8715
Viscosity 100 °C	cSt		14.9
Viscosity 40 °C	cSt	10	1.6
Viscosity Index		15	3
Flashpoint (ASTM D-2896)	°C		210
Sulphated ash	% Weight		1.09
T.B.N. (ASTM D-2896)	mg KOH/g		8.8
Pour point	°C		-33

#### Pennzoil Products Company

Note that the data quoted in this document are typical values and for indicative purposes only. The values do not constitute a commercial offer. Pennzoil Products Company reserves the right to amend product specifications without prior notice.