



SAE 10W-40 MOTOR OIL with Z-7[®]

PRODUCT DESCRIPTION:

Motor Oil with Z-7[®] is a mineral motor oil specifically for engines in passenger cars, light duty trucks and pleasure craft. The oil is recommended for gasoline and diesel engines, both turbocharged and naturally aspirated, where a performance level of API SJ/CF is required.

Motor Oil with Z-7[®] offers excellent protection against wear, rust and oxidation, as well as controlling engine deposits.

CHARACTERISTICS:

- excellent lubrication under cold start conditions
- high oxidation resistance
- reduces engine wear

EXCEEDS THE PERFORMANCE REQUIREMENTS OF:

API SJ/CF

ACEA A2/B2

TYPICAL PROPERTIES:

SAE		10W-40
Density (15.6°C)	kg/l	0.88
Viscosity 100°C	cSt	14.5
Viscosity 40°C	cSt	97.6
Viscosity Index		154
Flashpoint (ASTM D-92)	°C	202
Sulphated ash	% Weight	1.32
T.B.N. (ASTM D-2896)	mg KOH/g	9.8
Pour point	°C	-30

Pennzoil Products Company

Note that the data quoted in this document are typical values and for indicative purposes only. The values do not constitute a commercial offer. Pennzoil Products Company reserves the right to amend product specifications without prior notice.

Feb-09