



MOTORCYCLE OIL SAE 10W-40 SEMI-SYNTHETIC

PRODUCT DESCRIPTION:

Motorcycle Oil SAE 10W-40 Semi-Synthetic combines top quality synthetic and mineral oil base stocks to provide protection for 4-stroke motorcycle engines.

It is formulated to provide high levels of wear protection, oxidation resistance, as well as reducing engine deposits.

Special formulation characteristics ensure the proper functioning of oil-immersed ("wet") clutches

CHARACTERISTICS:

- rapid cold start
- reduces engine deposits
- excellent oxidation stability
- suitable for wet clutches
- protects against rust and corrosion

EXCEEDS THE PERFORMANCE REQUIREMENTS OF:

JASO MA

API SJ/SH/SG/SF

TYPICAL PROPERTIES:

SAE		10W-40
Density (15.6 °C)	kg/l	0.87
Viscosity 100 °C	cSt	14.9
Viscosity 40 °C	cSt	101.6
Viscosity Index		153
Flashpoint (ASTM D-92)	°C	210

Pennzoil Products Company

Note that the data quoted in this document are typical values and for indicative purposes only. The values do not constitute a commercial offer. Pennzoil Products Company reserves the right to amend product specifications without prior notice.

FEBR.09

Sulphated ash	% Weight	1.09
T.B.N. (ASTM D-2896)	mg KOH/g	8.8
Pour point	°C	-33

Pennzoil Products Company

Note that the data quoted in this document are typical values and for indicative purposes only. The values do not constitute a commercial offer. Pennzoil Products Company reserves the right to amend product specifications without prior notice.

FEBR.09