



MOTORCYCLE OIL SAE 10W-40 FULL SYNTHETIC

PRODUCT DESCRIPTION:

Motorcycle Oil SAE 10W-40 Full Synthetic has been developed for modern 4-stroke motorcycles operating at high engine speeds. Synthetic basestocks provide a high level of protection against oxidation, wear and engine deposits, and enhanced lubricity. It contains an additive system developed to provide extra protection against wear, deposits and oxidation, especially for highly stressed motorcycle engines.

CHARACTERISTICS:

- rapid lubrication under cold start conditions
- prevents build-up of deposits
- excellent oxidation stability
- suitable for "wet clutches"

SPECIFICATION:

JASO MA

API SL/SJ/SH/SG

TYPICAL PROPERTIES:

SAE		10W-40
Density (15.6 °C)	kg/l	0.85
Viscosity 100 °C	cSt	14.7
Viscosity 40 °C	cSt	95
Viscosity Index		161
Flashpoint (ASTM D-92)	°C	217
Sulphated ash	% Weight	1.09
T.B.N. (ASTM D-2896)	mg KOH/g	8.8
Pour point	°C	-51

Pennzoil Products Company

Note that the data quoted in this document are typical values and for indicative purposes only. The values do not constitute a commercial offer. Pennzoil Products Company reserves the right to amend product specifications without prior notice.
Febr.2010

Pennzoil Products Company

Note that the data quoted in this document are typical values and for indicative purposes only. The values do not constitute a commercial offer. Pennzoil Products Company reserves the right to amend product specifications without prior notice.

Febr.2010